AS Heavy Duty (ASHD) Series Connectors















ASHD14-1 (1x AWG 4)



AS 22-24320 (2 x AWG 4, 3 x AWG 20)





Autosport design for high current

motorsport applications • Early break / Late mate on data

Cable accommodation from

 Positive locking coupling mechanism **High performance materials** • Environmentally sealed

• Crimp type solid and gold plated

contacts for safety

• Thermal cycle tested • Heavy duty rated

copper contacts

16mm² - 70mm²

AS 24-34220 (3 x AWG 4, 2 x AWG 20)



AS 24-44420 (4 x AWG 4, 4 x AWG 20)

All dimensions are in mm unless otherwise stated.

CONTACTS & TOOLING PART NUMBERS

Contact Size	Socket	Pin	Filler Plug	Ins/Ext Tool	Crimp Tool	Socket Positioner	Pin Positioner
20	38943-20	38941-20	600300-20	M81969/14-10	M22520/2-01	M22520/2-10	M22520/2-10

Please note: PCB versions are ordered with AS2 prefixes and come with contacts.

_									
	Wire Size	Split-Finger Socket	Hyperboloid Socket	Pin	Ext Tool	Crimp Tool	Jaws	Contact	Max. Current
_	16mm	611103-016	605739	605734	610176		605774	20	7.5
	25mm	611103-025	605654	605660	610136- Tool	605775	605775	4	200
	35mm	611103-035	605740	605735			605776	0 **	300

^{*}For use with part numbers ASHD022-24320SN-S04 and ASHD622-24320PN-004

Application Note: Due to potential high current, we would recommend that the product be suitably insulated with the appropriate materials.

ACHD *

ORDERING INFORMATION

	ASHD	*	*	_	*	*	*	-	***	- ***
Range Ref:										
Style: 0 1 2 (ASHD size 14 only) 6										
Shell Size: 14 = ASHD 22 = ASHD 2-Way and SuperASHD 24 = ASHD 3 and 4-Way										
Contact Arrangement: 1 = (ASHD) 24320 = (size 22) 34220 = (size 24) 3-Way 44420 = (size 24) 4-Way 1 = (Super ASHD)										
Insert Type: P = Pin S = Socket										
Shell Keyways: N = Red (standard) A = Yellow B = Blue C = Orange D = Green E = Grey										
Harsh Environment: Contact Size Code 016 025 035										
Modification Code:										

36